



DATE: November 11, 2008
FOR IMMEDIATE RELEASE

CIT Relay & Switch announces RoHS, 20amp UL F Class rated J107F Relay

Minneapolis, Minnesota – The J107F Series relay offered by CIT Relay & Switch is UL F Class rated standard. Small in size and robust this relay is UL certified at many load include 20A at 125VAC/16VDC and 1/3hp at 277VAC. The rugged J107F is low in cost and offers coil power choices of .36W, .45W and .80W. Coil voltage choices range from 3VDC to 48VDC.

Contact Data: Contact arrangements are 1A = SPST N.O., 1B = SPST N.C., & 1C = SPDT. Contact ratings are 6A@277VAC, 10A@250VAC & 28VDC. 12A@125VAC & 28VDC, 15A@125VAC, 20A@125VAC & 16VDC, 1/3 HP @ 125/277VAC. Contact resistance is less than 50 milliohms; contact material is AgSnO₂. Maximum switching power is 2500VA, 420W. Maximum switching voltage is 380VAC, 100VDC. Maximum switching current is 20A.

General Data: Electrical life is 100k cycles with mechanical life of 10M cycles. Insulation resistance is 100MΩ minimum at 500VDC. Coil to contact dielectric strength is 1500V rms minimum with contact to contact dielectric strength at 75V rms minimum. Shock resistance is 100m/s² for 11ms with vibration resistance of 1.5mm double amplitude. Operating temperature is -55°C to 125°C and storage temperature of -55°C to 155°C. Solderability is 260°C for 5 seconds.

Lead-time averages 8 to 9 weeks. Volume pricing ranges from **\$0.30** dependent on option choices. Contact us directly for a quote and sample to solve your relay needs.

Typical applications of the J107F Series Relay include HVAC, motor control, security and emergency lighting.

CIT RELAY & SWITCH, a division of Circuit Interruption Technology, Inc., manufactures a broad array of automotive, telecom, security, industrial and audio relays and switches in thru-hole, panel, and surface mount styles. *CIT RELAY & SWITCH* products are supported by a worldwide network of distributors and sales representatives. For more information about the *CIT RELAY & SWITCH* J107F Series or any of the CIT switch or relay products, contact *CIT RELAY & SWITCH*, 1152 Highway 10 NE, Minneapolis, MN 55432. Phone: 763-535-2339, Fax: 763-535-2194, E-Mail: sales@citswitch.com, Website: www.citswitch.com

Direct Link: <http://www.citrelay.com/Catalog%20pages/Relays/J107F%20Catalog.pdf>

Press Release Contact: Doreen Leppa
dleppa@citrelay.com
763-535-2339

Sales & Engineering Contact: Tony Schisler
tschisler@citrelay.com
763-535-2339

CIT Relay & Switch
1152 Highway 10 NE
Minneapolis, MN 55432
763-535-2339
www.citswitch.com
sales@citswitch.com

